

BSCI ID: 156-039551-000

慈溪市乐诺照明科技有限公司

CIXI LEONLUX TECHNOLOGY CO., LTD

ADD: NO.36 Xujia,Yiyuan Village, Zonghan Street, Cixi 315300, China

TEL: +86 159 6890 9490

FAX: +86 574 6321 0667

E-mail: manfred@leonlux.net lemon@leonlux.net

<http://www.leonlux.net>



2022-2023

leonlux®













ISO9001



E-catalogue



TABLE OF
CONTENTS

1 01-06	Multi-battery LED worklight		7 27-30	IK08 LED WORKLIGHT / SINGLE BRIGHTNESS IK08 RECHARGEABLE LED WORKLIGHT / SINGLE BRIGHTNESS	
2 07-08	Multi-battery LED worklight		8 31-32	ISPOT WORKLIGHT SERIES	
3 09-12	360°LED ECONOMICAL WORK LIGHT/ TOWER LIGHT		9 33-34	ECONOMICAL RECHARGEABLE LED WORKLIGHT	
4 13-20	360°LED STAND WORK LIGHT/ TOWER LIGHT 360° LED STAND WORK LIGHT/ TOWER LIGHT WITH BATTERY		10 35-36	RECHARGEABLE LED HAND LAMP LED RECHARGEABLE SENSOR HEADLAMP	
5 21-22	IK08 LED WORKLIGHT / TRIPLE BRIGHTNESS		11 37-45	LED Bulkhead Fixture	
6 23-26	IK08 LED WORKLIGHT / TWIN BRIGHTNESS IK08 LED WORKLIGHT WITH BATTERY / TWIN BRIGHTNESS		12 46-46	Building Telescopic Tripod	

Multi-battery LED worklight




-  LEDS SAVE ENERGY
-  30.000 HOURS LED LIFESPAN
-  BRIGHT LED LIGHT OUTPUT
-  ZERO MAINTENANCE
-  Rechargeable LED charge indicator

One Worklight. Many Battery Systems.

The worklightlights are extremely robust, impact-resistant and, with the interface technology to the battery systems, extremely powerful and efficient.



Hybrid Version




- Battery LED construction spotlight compatible with Bosch Professional, Makita, Dewalt, Milwaukee, Metabo CAS - maximum flexibility.
- LED work light with 5 m cable (H07RN-F 2 X 1.0mm²) with hybrid technology:
- Construction site spotlight with 3 switching levels (100% - 60% - 30%)
- and protection system for power tool batteries: protected against deep discharge, overheating (caused by high load currents) and battery errors.



Model	88A05AD		88A06AD	
Power	40W		60W	
Color Temperature	3000K/4000K/6500K		3000K/4000K/6500K	
Luminous Flux	4800lm		7000lm	
Dimensions	235x145x235mm		275x145x275mm	
Compatible battery	Bosch Professional	Metabo	Milwaukee +Dewalt	Makita
Cable designation	H07RN-F 2 x 1,0mm ²			
Degree of protection (IP)	IP54			

DC function only



- Battery LED construction spotlight compatible with Bosch Professional, Makita, Dewalt, Milwaukee, Metabo CAS - maximum flexibility.
- Construction site spotlight with 3 switching levels (100% - 60% - 30%)
- and protection system for power tool batteries: protected against deep discharge, overheating (caused by high load currents) and battery errors.



Model	88A05D		88A06D	
Power	40W		60W	
Color Temperature	3000K/4000K/6500K		3000K/4000K/6500K	
Luminous Flux	4800lm		7000lm	
Dimensions	235x145x235mm		275x145x275mm	
Compatible battery	Bosch Professional	Metabo	Milwaukee +Dewalt	Makita
Degree of protection (IP)	IP54			



LEDS SAVE ENERGY



30.000 HOURS LED LIFESPAN



BRIGHT LED LIGHT OUTPUT



ZERO MAINTENANCE




AC function only

For indoor and outdoor use, IP 54.

- Pleasant, glare-free working light and special light scattering for extensive illumination.
- Light and still very robust.
- Low heat generation, no danger of injury.
- SMD LEDs have a very long lifespan, are shock-proof and maintenance-free.
- Fracture- and impact-proof plastic housing with rubber protection.
- With illuminated ON/OFF switch.



Model	88A05A	88A06A
Power	40W	60W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	4800lm	7000lm
Dimensions	235x145x235mm	275x145x275mm
Number of socket outlets	2	
Cable	H07RN-F 3G x 1,5mm ²	
Energy efficiency class		
Degree of protection (IP)	IP54	

Multi Battery LED worklight



Rechargeable
LED charge
indicator



30.000 HOURS
LED LIFESPAN



BRIGHT LED
LIGHT OUTPUT



ZERO
MAINTENANCE



Compatible with 18 V batteries




- One worklight. Many Battery Systems.
- Thanks to the Multi Battery 18V System,
- the extremely robust and bright Multi Battery LED worklights
- are compatible with 18V rechargeable batteries from the five largest
- power tool manufacturers.



Model	88A02D			
Power	15W			
Color Temperature	3000K/4000K/6500K			
Luminous Flux	1500lm			
Dimensions	135x135x142mm			
Compatible battery	Bosch Professional	Metabo	Milwaukee +Dewalt	Makita
Degree of protection (IP)	IP20			

360°LED ECONOMICAL
WORK LIGHT/ TOWER LIGHT



- 360° Radiation
- Flickering Free
- High Output Lumen
- IP69K

- Excellent all-round lighting thanks to 360° beam angle, anti-glare and wide diffusion.
- Robust, break and impact resistant plastic casing.

Model	35B03	35B04
Power	60W	80W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	6900lm	8400lm
Transport Dimensions	Ø 160x1300mm	Ø 160x1600mm
Dimensions In Use	Ø 970x2300mm	Ø 970x2900mm
Cable	H07RN-F 2 x 1.50mm²	
Energy efficiency class		
Degree of protection (IP)	IP69K	

360°LED ECONOMICAL
WORK LIGHT/ TOWER LIGHT



LEDS SAVE ENERGY



30.000 HOURS LED LIFESPAN



BRIGHT LED LIGHT OUTPUT



ZERO MAINTENANCE



360° Radiation



Flickering Free



High Output Lumen



IP69K

- Excellent all-round lighting thanks to 360° beam angle, anti-glare and wide diffusion.
- Robust, break and impact resistant plastic casing.



6900 LUMEN



8400 LUMEN

Model	35A03	35A04
Power	60W	80W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	6900lm	8400lm
Transport Dimensions	Ø 160x1300mm	Ø 160x1600mm
Dimensions In Use	Ø 500x1300mm	Ø 500x1600mm
Cable	H07RN-F 2 x 1.50mm²	
Energy efficiency class		
Degree of protection (IP)	IP69K	

360°LED STAND

WORK LIGHT/ TOWER LIGHT

Plastic legs available



Steel legs available



360°LED STAND WORK LIGHT/ TOWER LIGHT





360°
Radiation



Flickering
Free



High Output
Lumen



IP69K

- Excellent all-round lighting thanks to 360°beam angle, anti-glare and wide diffusion.

- Robust, break and impact resistant plastic casing.



70MM
TUBE DIA



IK10



11000
LUMEN



14500
LUMEN

Model	33A03D	33A04D
Power	90W	120W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	11000lm	14500lm
Transport Dimensions	170x186x1250mm	170x186x1480mm
Dimensions In Use	Ø 740x1290mm	Ø 740x1520mm
Cable	H07RN-F 2 x 1.50mm ²	
Energy efficiency class		
Degree of protection (IP)	IP69K	





360°
Radiation



Flickering
Free



High Output
Lumen



IP69K

- Excellent all-round lighting thanks to 360°beam angle, anti-glare and wide diffusion.

- Robust, break and impact resistant plastic casing.



90MM
TUBE DIA



18000
LUMEN



20000
LUMEN

Model	33A05D	33A06D
Power	150W	180W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	18000lm	20000lm
Transport Dimensions	190x170x1280mm	190x170x1520mm
Dimensions In Use	Ø 740x1375mm	Ø 740x1615mm
Cable	H07RN-F 2 x 1.50mm ²	
Energy efficiency class		
Degree of protection (IP)	IP69K	

360°LED STAND

WORK LIGHT/ TOWER LIGHT




TUBE DIA



Model	31C03D	31C04D
Power	90W	120W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	11000lm	14500lm
Transport Dimensions	170x186x1320mm	170x186x1560mm
Dimensions In Use	Ø 740x1340mm	Ø 740x1580mm
Number of socket outlets	2	
Cable	H07RN-F 3G x 1,5mm²	
Energy efficiency class		
Degree of protection (IP)	IP54	

- Excellent all-round lighting thanks to 360°beam angle, anti-glare and wide diffusion.
- Switch with light functions 100 - 50 %.
- Robust, break and impact resistant plastic casing.
- Splash-proof socket with self-closing cover.
- With ON/OFF switch.




TUBE DIA



Model	31C05D	31C06D
Power	150W	180W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	18000lm	20000lm
Transport Dimensions	190x170x1360mm	190x170x1600mm
Dimensions In Use	Ø 740x1380mm	Ø 740x1620mm
Number of socket outlets	2	
Cable	H07RN-F 3G x 1,5mm²	
Energy efficiency class		
Degree of protection (IP)	IP54	

- Excellent all-round lighting thanks to 360°beam angle, anti-glare and wide diffusion.
- Robust, break and impact resistant plastic casing.
- Splash-proof socket with self-closing cover.
- With ON/OFF switch.

360° LED STAND
WORK LIGHT/ TOWER LIGHT WITH BATTERY



Powerbank Function
Charge for your device



IPAD



Iphone



Battery version
With integrated Li-Ion battery, battery status display, overcharge and deep discharge protection, 2 switching levels: 100 %, 50 % for longer light duration. Always bright working light even in places without a power connection

A product image of the tower light with three feature icons: "360° Radiation", "Flickering Free", and "High Output Lumen".

Always bright working light even in places without power supply. Integrated Li-Ion battery.


- With integrated overcharge and deep discharge protection and battery status indicator.
- Battery and charge indicator with low battery warning.
- 2 switching levels: 100 %, 50 % light for longer light duration.
- Stainless dim function for 10%to 100%light.
- With 1.5m charging cable.
- Solid, modern aluminium housing.
- Floodlight can be continuously swivelled and locked with one hand by means of a quick release fastener.
- Sturdy tubular steel frame with plastic protective corners and ergonomically shaped plastic carrying handle

Model	31R02	31R03
Power	40W	60W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luninous Flux	1500lm/3000lm	2250lm/4500lm
Transport Dimensions	170x186x1020mm	170x186x1320mm
Dimensions In Use	Ø 740x1020mm	Ø 740x1320mm
Attery voltage	14.8V	14.8V
Battery capacity	4.4Ah	6.6Ah
Degree of protection (IP)	IP54	

IK08 LED WORKLIGHT / TRIPLE BRIGHTNESS



Procedure



- LEDs SAVE ENERGY
- 30,000 HOURS LED LIFESPAN
- BRIGHT LED LIGHT OUTPUT
- ZERO MAINTENANCE

Outlet Socket



TECHNOLOGY



- For indoor and outdoor use, IP 54.
- Pleasant, glare-free working light and special light scattering for extensive illumination.
 - Light and still very robust.
 - Low heat generation, no danger of injury.
 - SMD LEDs have a very long lifespan, are shock-proof and maintenance-free.
 - Fracture- and impact-proof plastic housing with rubber edge protection.
 - With illuminated ON/OFF switch.
 - Suitable for mounting on 6037 and 6038 tripods.



Model	92A08	92A08A
Power	80W	80W+2x30W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	6400lm	11000lm
Dimensions	300x90x360mm	375x120x360mm
Number of socket outlets	2	
Cable	H07RN-F 3G x 1,5mm²	
Energy efficiency class		
Degree of protection (IP)	IP54	

IK08 LED WORKLIGHT / TWIN BRIGHTNESS



LEDS SAVE ENERGY



30.000 HOURS LED LIFESPAN




BRIGHT LED LIGHT OUTPUT




ZERO MAINTENANCE

Procedure




ON/OFF Switch

2 Light Modes



Anti glare diffused lenses





- Excellent all-round lighting thanks to 270° beam angle, anti-glare and wide diffusion.
- Switch with light functions 100 - 50 %.
- The light can be used when placed upright, hanging or mounted on a stand.
- Robust, break and impact resistant plastic casing.
- Splash-proof socket with self-closing cover.
- With ON/OFF switch.
- Suitable for mounting on 6037 and 6038 tripods.



Model	99A20	99A40
Power	2x20W	2x40W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	3600lm	7200lm
Dimensions	180x130x285mm	225x128x330mm
Number of socket outlets	1	2
Cable	H07RN-F 3G x 1,5mm ²	
Energy efficiency class		
Degree of protection (IP)	IP54	

IK08 LED WORKLIGHT WITH BATTERY / TWIN BRIGHTNESS



- Excellent all-round lighting thanks to 270° beam angle, anti-glare and wide diffusion.
- Stainless dim function for 10%to 100%light.
- The light can be used when placed upright, hanging or mounted on a stand.
- Robust, break and impact resistant plastic casing.
- Integrated lithium-ion battery with charging indicator.
- With ON/OFF switch.
- Suitable for mounting on 6037 and 6038 tripods.



Model	99R10	99R20
Power	2x10W	2x20W
Color Temperature	3000K/4000K/6000K	3000K/4000K/6000K
Luminous Flux	1500lm	2800lm
Dimensions	180x115x285mm	225x120x330mm
Attery voltage	3.7V	14.8V
Battery capacity	8.8Ah	4.4Ah
Degree of protection (IP)	IP54	

IK08 LED WORKLIGHT / SINGLE BRIGHTNESS



Outlet Socket





For indoor and outdoor use, IP 54.

- Pleasant, glare-free working light and special light scattering for extensive illumination.
- Light and still very robust.
- Low heat generation, no danger of injury.
- SMD LEDs have a very long lifespan, are shock-proof and maintenance-free.
- Fracture- and impact-proof plastic housing with rubber protection.
- With illuminated ON/OFF switch.
- Suitable for mounting on 6037 and 6038 tripods.



Model	98A02	98A03	98A05
Power	20W	30W	50W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	1600lm	2400lm	4000lm
Dimensions	220x95x235mm	230x100x295mm	265x110x345mm
Number of socket outlets	2		
Cable	H07RN-F 3G x 1,5mm²		
Energy efficiency class			
Degree of protection (IP)	IP54		



For indoor and outdoor use, IP 54.

- Pleasant, glare-free working light and special light scattering for extensive illumination.
- Stainless dim function for 10%to 100%light.
- Light and still very robust.
- Low heat generation, no danger of injury.
- SMD LEDs have a very long lifespan, are shock-proof and maintenance-free.
- Fracture- and impact-proof plastic housing with rubber protection.
- With illuminated ON/OFF switch.
- Suitable for mounting on 6037 and 6038 tripods.

IK08 RECHARGEABLE
LED WORKLIGHT / SINGLE BRIGHTNESS



Model	98R02	98R03	98R05
Power	20W	30W	50W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	1500lm	2100lm	3500lm
Dimensions	220x90x230mm	230x105x295mm	265x110x345mm
Attery voltage	7.4V	14.8V	14.8V
Battery capacity	4.4Ah	4.4Ah	6.6Ah
Degree of protection (IP)	IP54		


ISPOT WORKLIGHT SERIES



For indoor and outdoor use, IP 65.

- Pleasant, glare-free working light and special light scattering for extensive illumination.
- Light and still very robust.
- Low heat generation, no danger of injury.
- SMD LEDs have a very long lifespan, are shock-proof and maintenance-free.
- Fracture- and impact-proof plastic housing with rubber edge protection.
- Suitable for mounting on 6037 and 6038 tripods.



Model	90B02	90B03	90B05	90B06
Power	20W	30W	50W	60W
Color Temperature	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
Luminous Flux	1600lm	2400lm	4000lm	4800lm
Dimensions	170x35x192mm	195x40x220mm	255x40x285mm	307x40x343mm
Cable	H05RN-F 3G x 1,0mm²			
Energy efficiency class				
Degree of protection (IP)	IP65			



LEDs SAVE ENERGY



30.000 HOURS LED LIFESPAN



BRIGHT LED LIGHT OUTPUT



ZERO MAINTENANCE

ECONOMICAL RECHARGEABLE LED WORKLIGHT



Rechargeable
LED charge
indicator



30,000 HOURS
LED LIFESPAN



BRIGHT LED
LIGHT OUTPUT



ZERO
MAINTENANCE



- Excellent all-round lighting thanks to 120° beam angle, anti-glare and wide diffusion.
- Switch with light functions 100 - 10 %.
- The light can be used when placed upright, hanging or mounted on a stand.
- Robust, break and impact resistant plastic casing.
- Integrated lithium-ion battery with charging indicator.
- With ON/OFF switch.
- Suitable for mounting on 6037 and 6038 tripods.



Model	96A01M	96A02M
Power	10W	20W
Color Temperature	3000K/4000K/6000K	3000K/4000K/6000K
Luminous Flux	700lm	1400lm
Dimensions	143x45x170mm	180x65x195mm
Attery voltage	3.7V	3.7V
Battery capacity	4.4Ah	8.8Ah
Degree of protection (IP)	IP54	

Rechargeable LED Hand Lamp



- With super-bright COB LED at the front.
- Additional switching step for 1 SMD LED in the lamp head.
- Working mode: High - Low - OFF - Top
- Rubberised for improved impact resistance and optimal grip
- Adjustable up to +/- 60° with integrated magnet.
- 2 magnets at the back and fold-out hook for flexible use.
- Integrated Li-Ion battery with charging indicator.
- USB charging interface, including USB charging cable.

			
Model	6848	6847	6846
Power	2W	3W	5W
Color Temperature	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
Luminous Flux	120lm	240lm	420lm
Dimensions	48x30x116mm	52x32x163mm	60x32x190mm
Attery voltage	3.7V	3.7V	3.7V
Battery capacity	1.0Ah	2.2Ah	4.4Ah
Degree of protection (IP)		IP54	

LuxPremium LED Rechargeable Sensor Headlamp



- With extremely bright LED.
- Two operating modes: manual and infrared sensor.
- Infrared sensor for hands-free operation.
- Working mode: High - Low.
- Tail light red, red flashing.
- Infinitely focus from laminary light nearby to high beam focused light.
- Battery pack on the back of the head for good balance.
- Exchangeable lithium-ion battery with charging indicator.
- Focus angle can be adjusted.
- USB charging cable included.



Model	HD1001A
Power	2W
Color Temperature	3000K/4000K/6000K
Luninous Flux	150lm
Dimensions	25x80mm
Attery voltage	3.7V
Battery capacity	2.2Ah
Degree of protection (IP)	IP54

LED Bulkhead Fixture

1) On/OFF Function (stand-by period be set to "0"s)




- 1 With sufficient ambient light, the light will not be switched on even if with motion signal.
- 2 With insufficient ambient light, the sensor switches on the light when motion is detected.
- 3 After elapse of hold time, the sensor switches off the light when no motion is detected.

2) 2-step dimming function (stand-by period be set to "+∞")



- 1 If there is no motion detected, the light will be remained at a low light level all the time.
- 2 When motion is detected, the sensor will switch on the light to 100% brightness.
- 3 After elapse of hold time, the sensor dims the light at the present low light level if no motion is detected.

3) 3-step dimming function (stand-by period be set to "10S/1min/3min/5min/10min/30min")




- 1 With sufficient ambient light, the light will not be switched on even if with motion signal.
- 2 With insufficient ambient light, the sensor switches on the light when motion is detected.
- 3 After elapse of hold time, the sensor dims the light at a low light level if no new motion is detected.
- 4 After elapse of standby period, the sensor switches off the light if no motion is detected in the detection zone.



- Compact LED oval lamp made of plastic with a translucent cover.
 - Suitable for mounting on either walls or ceilings.
 - User-friendly assembly thanks to external, water-tight connection terminal.
 - LEDs have a very long lifespan, are shock-proof and maintenance-free.
- Additionally for model with PIR:
- Detection range up to 8 metres, detection angle approx. 180°.
 - Switch-on time adjustable up to 60 seconds.



Master/Slave Wiring:



Model	BLK-1	BLK-1(Sensor)	BLK-1(emergency Kits)	BLK-1(Sensor + emergency)
Power	18W/14W/11W/8W	18W/14W/11W/8W	18W/14W/11W/8W	18W/14W/11W/8W
Color Temperature	3000K/4000K/6500K	3000K/4000K/6500K	3000K/4000K/6500K	3000K/4000K/6500K
Luminous Flux	2160lm/1680lm/1320lm/960lm	2160lm/1680lm/1320lm/960lm	2160lm/1680lm/1320lm/960lm	2160lm/1680lm/1320lm/960lm
Dimensions	Ø 300x71mm	Ø 300x71mm	Ø 300x71mm	Ø 300x71mm
Sensor	No	Yes	No	Yes
Degree of protection (IP)	IP65	IP65	IP65	IP65

FL-1 Cruiser Aluminium Waterproof Fixture



Model	FL1-4FT-32W	FL1-4FT-40W	FL1-4FT-49W	FL1-4FT-55W	FL1-4FT-68W	FL1-4FT-81W	FL1-4FT-98W
Power	32W	40W	49W	55W	68W	81W	98W
Color Temperature	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K
Luminous Flux	5020lm	6280lm	7690lm	8630lm	10670lm	12710lm	15380lm
Dimensions	1200x94x78mm	1200x94x78mm	1200x94x78mm	1200x94x78mm	1200x94x78mm	1500x94x78mm	1500x94x78mm
Degree of protection (IP)	IP66+IK10						

FL-3 Waterproof Fixture



Model	FL3-2FT-17W	FL3-4FT-34W	FL3-5FT-46W	FL3-2FT-17W-S	FL3-4FT-34W-S	FL3-46FT-46W-S
Power	17W	34W	46W	17.5W	34.5W	46.5W
Color Temperature	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K
Luminous Flux	2450lm	4900lm	6630lm	2450lm	4900lm	6630lm
Dimensions	656x60x54mm	1206x60x54mm	1506x60x54mm	656x60x54mm	1206x60x54mm	1506x60x54mm
Degree of protection (IP)	IP66+IK08					

FL-4 Waterproof Fixture




Model	FL4-2FT-22W	FL4-4FT-34W	FL4-5FT-48W	FL4-2FT-22W-S	FL4-4FT-34W-S	FL4-5FT-48W-S
Power	22W	34W	48W	22.5W	34.5W	48.5W
Color Temperature	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K	4000K/5000K/6000K
Luminous Flux	2950lm	4550lm	6430lm	2950lm	4550lm	6430lm
Dimensions	600x70x64mm	1200x70x64mm	1500x70x64mm	600x70x64mm	1200x70x64mm	1500x70x64mm
Sensor	NO	NO	NO	YES	YES	YES
Degree of protection (IP)	IP66+IK08					

T45 Tubular Light Dia45mm PC Transparent Housing



Model	T45-PCT-2FT	T45-PCT-4FT	T45-PCT-5FT
Power	15W	30W	36W
Color Temperature	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K
Luminous Flux	2000lm	4000lm	4800lm
Dimensions	Ø45x612mm	Ø45x1172mm	Ø45x1452mm
Degree of protection (IP)	IP69K+IK08		

T70 Tubular Light Dia70mm PC Opal Housing



Model	T70-PCO-2FT	T70-PCO-4FT	T70-PCO-5FT	T70-PCO-2FT-S	T70-PCO-4FT-S	T70-PCO-5FT-S
Power	19W	38W	50W	19.5W	38.5W	50.5W
Color Temperature	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K
Luminous Flux	2910lm	5810lm	7650lm	2910lm	5810lm	7650lm
Dimensions	ø70x712mm	ø70x1272mm	ø70x1552mm	ø70x712mm	ø70x1272mm	ø70x1552mm
Sensor	NO	NO	NO	YES	YES	YES
Degree of protection (IP)	IP69K+IK10					

T70 Tubular Light Dia70mm PMMA Opal Housing Farm Application




Model	T70-PMO-2FT	T70-PMO-4FT	T70-PMO-5FT
Power	19W	38W	50W
Color Temperature	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K
Luminous Flux	2850lm	5700lm	7500lm
Dimensions	ø70x712mm	ø70x1272mm	ø70x1552mm
Degree of protection (IP)	IP69K+IK10		

T90 Tubular Light Dia90mm PC Opal Housing






Model	T90-PCO-2FT	T90-PCO-4FT	T90-PCO-5FT	T90-PCO-2FT-S	T90-PCO-4FT-S	T90-PCO-5FT-S
Power	22W	44W	58W	22.5W	44.5W	58.5W
Color Temperature	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K	3000K/4000K/5000K
Luminous Flux	3320lm	6640lm	8760lm	3320lm	6640lm	8760lm
Dimensions	Ø90x706mm	Ø90x1265mm	Ø90x1545mm	Ø70x712mm	Ø70x1272mm	Ø70x1552mm
Sensor	NO	NO	NO	YES	YES	YES
Degree of protection (IP)	IP69K+IK10					


Building Telescopic Tripod



Hinged, extremely stable feet with ground mounting plates.

- Heavy-duty, stable and robust design.
- Strong stand pipes made of square steel profile, galvanically zinc-plated.
- Adjustable at any height up to max. 3.0 m.
- Solid attachment with anchor screws, alternatively with included handles.





Hinged, extremely stable feet with ground mounting plates.

- Heavy-duty, stable and robust design.
- Strong stand pipes made of square steel profile, galvanically zinc-plated.
- Adjustable at any height up to max. 1.5 m.
- Solid attachment with anchor screws, alternatively with included handles.